TECHNICAL DATA

TB300SD	TB900SD
300 Nm	900 Nm
140 1/min	52 1/min
285 x 58 x 220	315 x 68 x 220
3,5 kg	4,2 kg
3/4"	3/4"
	300 Nm 140 1/min 285 x 58 x 220 3,5 kg



- Case
- 2x rechargeable Li-Ion battery
- Charger
- Operation manual





ADDITIONAL EQUIPMENT



Slip-on torque support

- Square socket
- Material: Steel, hot dip galvanised
- Rubber handle

Telescopic extension

- Length: 790 mm 1400 mm
- Stainless steel rod
- Operating socket: 27/32; 12/14 (malleable cast iron, electrolytically galvanised)
- Machine connection: 3/4"

Revolution counter

- 8-digit LCD-Display
- Lithium battery
- TP5/
- · Maintenance free
- Reset-button

Mains adaptor

- 220V
- Cord: 5m



Our staff is happy to assist with individual solutions.





KETTLER GmbH

Köhlerstraße 8
46286 Dorsten-Wulfen, Germany
Telephone (+49 23 69) 91 82-0
Telefax (+49 23 69) 91 82-91
info@kettlerweb.de
www.kettlerweb.de

lotice

Additional information is available in our detailed catalogue.

You will find the corresponding download link on our website www.kettlerweb.de or by scanning the QR-Code above with your smartphone or tablet.

-/----/----

of 08.2018 Technical

TORQUE WRENCH

torcbrain



